

PROJECTION LENSES - FOR LIGHT GUIDES

DIMENSIONS	PART NUMBER	LENS DIAMETER	LIGHT GUIDE FIBER BUNDLE DIAMETER	"A" APPROX. MAX DIST. FROM TARGET	"B" APPROX. DIA. SIZE OF INFRARED BEAM
	CMLH500 (PLASTIC LENS)	0.50 INCHES (1.27CM)	.12 .06	1.125 1.125	.18 @ 1.25" .09 @ 1.25"
	CMLH501 (GLASS LENS)	0.50 INCHES (1.27CM)	.12 .06	.875 .875	.12 @ .88" .06 @ .88"
	CMLH750	0.75 INCHES (1.9CM)	.12 .06	9.00" 4.00"	.25 @ 3.00" .12 @ 3.00"
	CMLH1050	1.00 INCH (2.5CM)	.12 .06	20.00" 14.00"	.69 @ 12.00" .38 @ 12.00"
	CML16F	1.00 INCH (2.5CM)	.12 .06	16.00" 12.00"	.50 @ 6.00" .25 @ 6.00"

ILLUMINATOR WITH LIGHT GUIDE ADAPTOR

DIMENSIONS	PART NUMBER	DESCRIPTION
	CMI-150	THE HIGH INTENSITY LIGHTSOURCE FEATURED, MODEL CMI-150, INCLUDES A 150 WATT QUARTZ HALOGEN LAMP WHICH IS FAN COOLED WITH INTENSITY ADJUSTMENT, LAMP LIFE 200-1800 HOURS, 3300%DK COLOR TEMPERATURE.